


Rated Voltage	Power	Rated Torque	Maximum Torque	Rated Speed	Maximum Speed	Rated Phase Current	Max Phase Current	Power Wire				Terminal A						Temperature Sensor					
48VDC	800W	40N.m	80N.m	200RPM	300RPM	20A	40A	Pin	NC	NC	NC	Pin	5	4	3	9	6	14	13	12	11	NC	NC
Wheel Diameter	Weight	Shaft Type	Encoder	Tire	Brake Type	Protection Level	Suggested Load	Color	Blue	Yellow	Green	Color	Black	Red	Yellow	Blue	Green	Brown	Brown Black	Grey	Grey Black	White	White Black
266mm	9.5KG	Double shaft	1024-wire optical encoder	Rubber	Electric brake	IP65	300KG	Signal	Power Wire: W	Power Wire: U	Power Wire: V	Signal	GND	+5V	Hall U	Hall W	Hall V	Encoder A+	Encoder A-	Encoder B+	Encoder B-	Thermistor +	Thermistor -



Design change

- 1
- 2
- 3
- 4

View



ERP:

Design:

Date:

Company Name: **YTK Co., Ltd**

Proofread:

Date:

Product Name: **Hub Servo Motor**

Approve:

Date:

Product P/N: **ZLLG10ASM800 V1.0(Double Shaft)**