


RB-30GM

02 & 03 TYPE



外形尺寸/ Appearance Size



unit:mm

齒輪馬達轉矩 & 速度/ Geared Motor Torque & Speed

減速比 Reduction ratio		1/20	1/30	1/36	1/50	1/60	1/75	1/90	1/100	1/120	1/150	1/180	1/200	1/250	1/300	1/400	1/500	1/600	1/810	1/900	1/1000
12V	定格扭力 Rated torque (kg-cm)	1	1.5	1.5	2	2	3	3	3	4	4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
	定格轉數 Rated speed (rpm)	255	168	150	107	91	73	62	56	46.3	37.5	32	28.8	24	19.5	15.2	12.1	10.4	7.7	6.9	6.3
24V	定格扭力 Rated torque (Kg-cm)	1	1.5	1.5	2	2	3	3	3	4	4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
	定格轉數 Rated speed (rpm)	258	168	150	107	91	73	62	56	46.3	37.4	31.8	28.7	24	19.5	15.1	12.1	10.3	7.7	6.9	6.3
軸心迴轉方向 Rotation direction		CCW																			
長度 Length (L)		23										28									

馬達單體型式/ Motor Data

定格電壓 Rated volt (V)	定格扭力 Rated torque (g-cm)	定格轉數 Rated speed (rpm)	定格電流 Rated current (mA)	無負荷轉數 No load speed (rpm)	無負荷電流 No load current (mA)	定格出力 Rated output (W)	重量 Weight (g)
12	78	5290	≤ 530	6500	≤ 150	4.22	73
24	74	5250	≤ 250	6500	≤ 85	3.97	73

馬達單體特性/ Motor Characteristics

