


IG-38PGM

01 & 02 TYPE



外形尺寸/ Appearance Size



unit:mm

齒輪馬達轉矩 & 速度/ Geared Motor Torque & Speed

減速比 Reduction ratio		1/5	1/14	1/19	1/27	1/51	1/71	1/100	1/139	1/189	1/264	1/516	1/721				
12V	定格扭力 Rated torque (Kg-cm)	1	2.4	3.3	4.7	7.6	10	15	20	23	25	30	30				
	定格轉數 Rated speed (rpm)	1100	420	300	210	110	81	58	41	30	22.5	11.6	8.4				
24V	定格扭力 Rated torque (Kg-cm)	1.1	2.7	3.7	5.2	8.5	12	16	20	25	25	30	30				
	定格轉數 Rated speed (rpm)	1050	390	280	200	105	76	55	41	29	22.5	11.6	8.4				
軸心迴轉方向 Rotation direction		CCW															
長度 Length (L)		33.1		41.8				50.5				59.2					

馬達單體型式/ Motor Data

定格電壓 Rated volt (V)	定格扭力 Rated torque (g-cm)	定格轉數 Rated speed (rpm)	定格電流 Rated current (mA)	無負荷轉數 No load speed (rpm)	無負荷電流 No load current (mA)	定格出力 Rated output (W)	重量 Weight (g)
12	250	5800	≤ 1600	6400	≤ 300	14.89	264
24	280	5500	≤ 900	6400	≤ 160	15.81	266

馬達單體特性/ Motor Characteristics

