

品番	ストローク (mm)	最大推力 (N)	電圧/最大電流 DC V / A	最大保持 力(N)	最大負荷 速度(mm/sec.)	無負荷速度 (mm/sec.)	サイズ (mm)	重量 (kg)
ELA26-050-005-XX	50	50	24/0.8, 12/1.5	35	66.2	150.0	Φ26*232	0.29
ELA26-050-020-XX	50	200	24/0.8, 12/1.5	170	13.9	31.6	Φ26*232	0.29
ELA26-050-050-XX	50	500	24/0.8, 12/1.5	500	5.0	11.3	Φ26*232	0.29
ELA26-050-100-XX	50	1,000	24/0.8, 12/1.5	840	2.6	5.8	Φ26*232	0.29
ELA26-100-005-XX	100	50	24/0.8, 12/1.5	35	66.2	150.0	Φ26*282	0.33
ELA26-100-020-XX	100	200	24/0.8, 12/1.5	170	13.9	31.6	Φ26*282	0.33
ELA26-100-050-XX	100	500	24/0.8, 12/1.5	500	5.0	11.3	Φ26*282	0.33
ELA26-100-100-XX	100	1,000	24/0.8, 12/1.5	840	2.6	5.8	Φ26*282	0.33
ELA26-150-005-XX	150	50	24/0.8, 12/1.5	35	66.2	150.0	Φ26*332	0.37
ELA26-150-020-XX	150	200	24/0.8, 12/1.5	170	13.9	31.6	Φ26*332	0.37
ELA26-150-050-XX	150	500	24/0.8, 12/1.5	500	5.0	11.3	Φ26*332	0.37
ELA26-150-100-XX	150	1,000	24/0.8, 12/1.5	840	2.6	5.8	Φ26*332	0.37
ELA26-200-005-XX	200	50	24/0.8, 12/1.5	35	66.2	150.0	Φ26*382	0.41
ELA26-200-020-XX	200	200	24/0.8, 12/1.5	170	13.9	31.6	Φ26*382	0.41
ELA26-200-050-XX	200	500	24/0.8, 12/1.5	500	5.0	11.3	Φ26*382	0.41
ELA26-200-100-XX	200	1,000	24/0.8, 12/1.5	840	2.6	5.8	Φ26*382	0.41
ELA26-250-005-XX	250	50	24/0.8, 12/1.5	35	66.2	150.0	Φ26*432	0.45
ELA26-250-020-XX	250	200	24/0.8, 12/1.5	170	13.9	31.6	Φ26*432	0.45
ELA26-250-050-XX	250	500	24/0.8, 12/1.5	500	5.0	11.3	Φ26*432	0.45
ELA26-250-100-XX	250	1,000	24/0.8, 12/1.5	840	2.6	5.8	Φ26*432	0.45
ELA26-300-005-XX	300	50	24/0.8, 12/1.5	35	66.2	150.0	Φ26*482	0.49
ELA26-300-020-XX	300	200	24/0.8, 12/1.5	170	13.9	31.6	Φ26*482	0.49
ELA26-300-050-XX	300	500	24/0.8, 12/1.5	500	5.0	11.3	Φ26*482	0.49
ELA26-300-100-XX	300	1,000	24/0.8, 12/1.5	840	2.6	5.8	Φ26*482	0.49
ELA35-100-020-XX	100	200	24/2.5, 12/5.0	220	52.8	90.0	Φ35*342	0.66
ELA35-100-060-XX	100	600	24/2.5, 12/5.0	650	18.9	32.1	Φ35*342	0.66
ELA35-100-120-XX	100	1,200	24/2.5, 12/5.0	1,250	9.8	16.7	Φ35*342	0.66
ELA35-100-160-XX	100	1,600	24/2.5, 12/5.0	1,600	7.5	12.9	Φ35*342	0.66
ELA35-100-200-XX	100	2,000	24/2.5, 12/5.0	2,400	5.2	8.8	Φ35*342	0.66
ELA35-200-020-XX	200	200	24/2.5, 12/5.0	220	52.8	90.0	Φ35*442	0.78
ELA35-200-060-XX	200	600	24/2.5, 12/5.0	650	18.9	32.1	Φ35*442	0.78
ELA35-200-120-XX	200	1,200	24/2.5, 12/5.0	1,250	9.8	16.7	Φ35*442	0.78
ELA35-200-160-XX	200	1,600	24/2.5, 12/5.0	1,600	7.5	12.9	Φ35*442	0.78
ELA35-200-200-XX	200	2,000	24/2.5, 12/5.0	2,400	5.2	8.8	Φ35*442	0.78
ELA35-300-020-XX	300	200	24/2.5, 12/5.0	220	52.8	90.0	Φ35*542	0.90
ELA35-300-060-XX	300	600	24/2.5, 12/5.0	650	18.9	32.1	Φ35*542	0.90
ELA35-300-120-XX	300	1,200	24/2.5, 12/5.0	1,250	9.8	16.7	Φ35*542	0.90
ELA35-300-160-XX	300	1,600	24/2.5, 12/5.0	1,600	7.5	12.9	Φ35*542	0.90
ELA35-300-200-XX	300	2,000	24/2.5, 12/5.0	2,400	5.2	8.8	Φ35*542	0.90
ELA35-400-020-XX	400	200	24/2.5, 12/5.0	220	52.8	90.0	Φ35*642	1.02
ELA35-400-060-XX	400	600	24/2.5, 12/5.0	650	18.9	32.1	Φ35*642	1.02
ELA35-400-120-XX	400	1,200	24/2.5, 12/5.0	1,250	9.8	16.7	Φ35*642	1.02
ELA35-400-160-XX	400	1,600	24/2.5, 12/5.0	1,600	7.5	12.9	Φ35*642	1.02
ELA35-400-200-XX	400	2,000	24/2.5, 12/5.0	2,400	5.2	8.8	Φ35*642	1.02
ELA35-500-020-XX	500	200	24/2.5, 12/5.0	220	52.8	90.0	Φ35*742	1.14
ELA35-500-060-XX	500	600	24/2.5, 12/5.0	650	18.9	32.1	Φ35*742	1.14
ELA35-500-120-XX	500	1,200	24/2.5, 12/5.0	1,250	9.8	16.7	Φ35*742	1.14
ELA35-500-160-XX	500	1,600	24/2.5, 12/5.0	1,600	7.5	12.9	Φ35*742	1.14
ELA35-500-200-XX	500	2,000	24/2.5, 12/5.0	2,400	5.2	8.8	Φ35*742	1.14
ELA45-100-040-XX	100	400	24/5.0, 12/10.0	430	68.5	112.5	Φ45*397	1.13
ELA45-100-120-XX	100	1,200	24/5.0, 12/10.0	1,300	19.6	32.1	Φ45*397	1.13
ELA45-100-240-XX	100	2,400	24/5.0, 12/10.0	2,470	10.1	16.7	Φ45*397	1.13
ELA45-100-380-XX	100	3,800	24/5.0, 12/10.0	4,600	5.4	8.8	Φ45*397	1.13
ELA45-100-550-XX	100	5,500	24/5.0, 12/10.0	6,000	3.9	6.3	Φ45*397	1.13
ELA45-200-040-XX	200	400	24/5.0, 12/10.0	430	68.5	112.5	Φ45*497	1.32
ELA45-200-120-XX	200	1,200	24/5.0, 12/10.0	1,300	19.6	32.1	Φ45*497	1.32
ELA45-200-240-XX	200	2,400	24/5.0, 12/10.0	2,470	10.1	16.7	Φ45*497	1.32
ELA45-200-380-XX	200	3,800	24/5.0, 12/10.0	4,600	5.4	8.8	Φ45*497	1.32
ELA45-200-550-XX	200	5,500	24/5.0, 12/10.0	6,000	3.9	6.3	Φ45*497	1.32
ELA45-300-040-XX	300	400	24/5.0, 12/10.0	430	68.5	112.5	Φ45*597	1.51
ELA45-300-120-XX	300	1,200	24/5.0, 12/10.0	1,300	19.6	32.1	Φ45*597	1.51
ELA45-300-240-XX	300	2,400	24/5.0, 12/10.0	2,470	10.1	16.7	Φ45*597	1.51
ELA45-300-380-XX	300	3,800	24/5.0, 12/10.0	4,600	5.4	8.8	Φ45*597	1.51
ELA45-300-550-XX	300	5,500	24/5.0, 12/10.0	6,000	3.9	6.3	Φ45*597	1.51
ELA45-400-040-XX	400	400	24/5.0, 12/10.0	430	68.5	112.5	Φ45*697	1.70
ELA45-400-120-XX	400	1,200	24/5.0, 12/10.0	1,300	19.6	32.1	Φ45*697	1.70
ELA45-400-240-XX	400	2,400	24/5.0, 12/10.0	2,470	10.1	16.7	Φ45*697	1.70
ELA45-400-380-XX	400	3,800	24/5.0, 12/10.0	4,600	5.4	8.8	Φ45*697	1.70
ELA45-400-550-XX	400	5,500	24/5.0, 12/10.0	6,000	3.9	6.3	Φ45*697	1.70
ELA45-500-040-XX	500	400	24/5.0, 12/10.0	430	68.5	112.5	Φ45*797	1.89
ELA45-500-120-XX	500	1,200	24/5.0, 12/10.0	1,300	19.6	32.1	Φ45*797	1.89
ELA45-500-240-XX	500	2,400	24/5.0, 12/10.0	2,470	10.1	16.7	Φ45*797	1.89
ELA45-500-380-XX	500	3,800	24/5.0, 12/10.0	4,600	5.4	8.8	Φ45*797	1.89
ELA45-500-550-XX	500	5,500	24/5.0, 12/10.0	6,000	3.9	6.3	Φ45*797	1.89

「*XXは電圧を示し、12Vまたは24Vを選択可能です。」